Bar Screens

Amwell builds quality heavy duty front cleaned bar screens to your specifications in vertical or inclined designs in widths from 1 ft. to 7 ft. and depths to 30 ft. Choose from stainless steel or carbon steel construction. All models are powered by shaft mounted direct drive motors. Options include "pivot mounted design" for easy maintenance and more.

Choose Amwell bar screens as your first line of defense.

- Shaft mounted direct drive eliminates drive chain and sprocket maintenance
- Front cleaned
- Stainless or carbon steel construction
- Built for 1 ft. to 7 ft.
 widths and depths to 30 ft.
- Timer or liquid level controlled "run" cycles
- Stainless, cast iron or polymer coated rake chain
- 1/2" through 1-1/2" screen bar openings



AMWELL.



Ouality Your first line of defense.

Protect your downstream equipment from hazardous debris with reliable, Amwell bar screens.

Choose from stainless or carbon steel construction with widths from 1 ft. to 7 ft. and depths to 30 ft. All units feature shaft mounted direct drives controlled by either timers or differential liquid level controllers.

Pivoted designs allow the entire mechanism to pivot out of the channel for ease of maintenance. Front cleaned screens can be vertical or inclined at 75° or 84°.

Standard screen openings are 1/2" to 1-1/2". Screen rakes are driven by your choice of stainless steel, cast iron or polymer coated chain with metallic or non-metallic sprockets.

For comprehensive product specifications, drawings and additional options for any system, contact Amwell beadquarters, or your local Amwell Representative.



All bar screens are fully assembled and thoroughly shop tested to insure trouble-free operation prior to shipment. Units can be fabricated in sections to allow installation in existing structures.



600 N. Commons Drive, Suite 116 • Aurora, IL 60504 • Phone: 630-898-6900 • Fax: 630-898-1647

E-mail: amwell@amwell-inc.com • Internet: www.amwell-inc.com